



REVISION RECORD			
REV	ECD	DESCRIPTION	DATE
△		SNS螺丝变为8脚螺丝	05/13/08*
△		VDI额定电流由24A改为32A	06/16/08*
△		工号变更, 去掉绝缘板	Zengy 07/21/08*
△		品名中加上额定底高"1.2"	Zengy 09/03/08*
△		修改品名中"10A"为"100A"	LJH 11/06/08*
△		修改参数及刻字	LJH 02/12/09*
△		结构变更	hyq 06/03/09*
△		增加线径刻字	HYQ 08/03/09*

Notes:

- Pitch: 8.2mm, Poles: 2-12P
- Rated voltage/current: UL 300V/20A VDE 450V/32A
- Operation temperatures: -40°C ~ +105°C
- Withstanding Voltage: AC2000V/1Min
- Insulation Resistance: 5000MΩ/DC1000V
- Wire Range: 20~12AWG, 0.5-4.0mm²
- Max. Torque Value: M2.5, 4.08kgf.cm
- Undimensioned Tolerances:

Pitch range in mm	Nominal dimension range in mm	
	over	under
6	to 10	to 30
10	to 24	to 60
15	to 30	to 100
20	to 48	to 150

ITEM	DESCRIPTION	Q'TY	MATERIAL	NOTES
1	DEGSON-1.2 Housing	1	PA66	UL94V-2
2	DG8H"-Screws M2.5	XX*2	Steel	Cr ³⁺ Zn
3	DG8HS-Current carrier	XX	Steel	Cr ³⁺ Zn

DEGSON 宁波高压电子有限公司
DEGSON ELECTRONICS CO., LTD

NAME: DEGSON-1.2-XXP-1Y-100A (H)

DRAWING NO.: DG8HS-E06

FINISH:

SCALE: 1:1

THIRD ANGLE PROJECTION

DD NOT SCALE DRAWING

SHEET 1 OF 1