


Part Number	Maximum Allowable Voltage		Varistor Voltage V@0.1mA		Maximum Clamping Voltage V@ 5A (V)	Withstanding Surge Current		Rated Wattage (W)	Energy 10/1000 μ s (J)	UL	CSA	VDE
	ACrms (V)	DC (V)	(V)	Tolerance Range		1 Time (A)	2 Times (A)					
JVR20N180M11□△△	11	14	18	+ 20%	* 36	2000	1000	0.2	7.0	✓		✓
JVR20N220L 11□△△	14	18	22	+ 15%	* 43				8.0	✓		✓
JVR20N270K11□△△	17	22	27		* 53				10.0	✓		✓
JVR20N330K11□△△	20	26	33		* 65				12.0	✓		✓
JVR20N390K11□△△	25	31	39		* 77				14.0	✓		✓
JVR20N470K11□△△	30	38	47		* 93				17.0	✓		✓
JVR20N560K11□△△	35	45	56		* 110				20.0	✓		✓
JVR20N680K11□△△	40	56	68		* 135	6500	4000	1.0	24.0	✓		✓
JVR20N820K11□△△	50	65	82	+10%	135				44.0	✓		✓
JVR20N101K11□△△	60	85	100		165				56.0	✓		✓
JVR20N121K11□△△	75	100	120		200				64.0	✓		✓
JVR20N151K11□△△	95	125	150		250				88.0	✓		✓
JVR20N181K11□△△	115	150	180		300				104.0	✓		✓
JVR20N201K11□△△	130	170	200		340				114.0	✓	✓	✓
JVR20N221K11□△△	140	180	220		360				124.0	✓	✓	✓
JVR20N241K11□△△	150	200	240		395				134.0	✓	✓	✓
JVR20N271K11□△△	175	225	270		455				158.0	✓	✓	✓
JVR20N301K11□△△	195	250	300		505				168.0	✓	✓	✓
JVR20N331K11□△△	210	275	330		550				184.0	✓	✓	✓
JVR20N361K11□△△	230	300	360		595				208.0	✓	✓	✓
JVR20N391K11□△△	250	320	390		650				240.0	✓	✓	✓
JVR20N431K11□△△	275	350	430		710				264.0	✓	✓	✓
JVR20N471K11□△△	300	385	470		775				280.0	✓	✓	✓
JVR20N511K11□△△	320	418	510		842				296.0	✓	✓	✓
JVR20N561K11□△△	350	460	560		920				312.0	✓	✓	✓
JVR20N621K11□△△	385	505	620		1025				328.0	✓	✓	✓
JVR20N681K11□△△	420	560	680		1120				344.0	✓	✓	✓
JVR20N751K11□△△	460	615	750		1240				360.0	✓	✓	✓
JVR20N781K11□△△	485	640	780		1290				368.0	✓	✓	✓
JVR20N821K11□△△	510	670	820		1355				376.0	✓	✓	✓
JVR20N911K11□△△	550	745	910		1500				408.0	✓	✓	✓
JVR20N102K11□△△	625	825	1000		1650				448.0	✓	✓	✓
JVR20N112K11□△△	680	895	1100		1815				496.0	✓	✓	✓
JVR20N182K11□△△	1000	1465	1800		2970				695.0			

1) The clamping voltage from 180M to 680K are tested with current 20A.
For application required ratings not shown, contact RFE application engineering.

- : Lead Style
Y: vertical kink (standard)
P: straight leads
△△ : Lead Length / Packing Method



PULSE RATING CURVES

